

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.03.2024 Version number 304 (replaces version 303) Revision: 12.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier 600086
- · Trade name: <u>Rust Converter E-COLL</u>
- · Article number: 4317784425599, 4317784425605
- · UFI: QQGQ-GA46-SA0U-1WWT
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- **Product category** PC14 Metal surface treatment products
- · Application of the substance / the mixture Penetrating oil

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:
 E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH
 EDE Platz 1
 D-42389 Wuppertal
 Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

· 2.2 Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Warning



Printing date 12.03.2024

Version number 304 (replaces version 303)

Revision: 12.03.2024

Trade name: Rust Converter E-COLL

(Contd. of page 1)

· Hazard statements

H226 Flammable liquid and vapour.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Contains reaction mixture consisting of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Contains biocidal products: 1,2-benzisothiazol-3(2H)-one

· Labelling of packages where the contents do not exceed 125 ml

· Hazard pictograms



· Signal word Warning

· Hazard statements Void

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

· 2.3 Other hazards

- Results of PBT and vPvB assessment
- · PBT: Not applicable.

· vPvB: Not applicable.

(Contd. on page 3)

EU



Printing date 12.03.2024

Version number 304 (replaces version 303)

Revision: 12.03.2024

Trade name: Rust Converter E-COLL

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43-XXXX	ethanol	10-<25%	
CAS: 1336-21-6 EINECS: 215-647-6 Index number: 007-001-01-2 Reg.nr.: 01-2119488876-14	ammonia ♦ Skin Corr. 1B, H314 ♦ Aquatic Acute 1, H400 Specific concentration limit: STOT SE 3; H335: C ≥ 5 %	0-<1%	
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43-xxxx	butanone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	0.1-<1%	
CAS: 2634-33-5 EINECS: 220-120-9 Index number: 613-088-00-6	 1,2-benzisothiazol-3(2H)-one Èye Dam. 1, H318 Aquatic Acute 1, H400; Aquatic Chronic 2, H411 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 % 	<0.1%	
CAS: 55965-84-9 Index number: 613-167-00-5 Reg.nr.: 01-2120764691-48	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	<0.1%	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 4)

EU —



Printing date 12.03.2024

Version number 304 (replaces version 303)

Revision: 12.03.2024

Trade name: Rust Converter E-COLL

(Contd. of page 3)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air.
- After skin contact: Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed Dizziness Headache Nausea
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- Protective equipment:

Do not inhale explosion gases or combustion gases. Wear self-contained respiratory protective device.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:
- Dilute with plenty of water.

Prevent seepage into sewage system, workpits and cellars.



Printing date 12.03.2024

Version number 304 (replaces version 303)

Revision: 12.03.2024

Trade name: Rust Converter E-COLL

(Contd. of page 4)

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:



Keep ignition sources away - Do not smoke.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Well cosed, protected from light.
- Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 78-93-3 butanone

IOELV Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.



Printing date 12.03.2024

Version number 304 (replaces version 303)

Revision: 12.03.2024

Trade name: Rust Converter E-COLL

(Contd. of page 5)

• Respiratory protection: Not necessary if room is well-ventilated.

Hand protection



Protective gloves

· Material of gloves

Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Recommendation: safety glasses with side protection shield

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical properties			
· General Information	Dia di		
· Colour:	Black		
· Odour:	Characteristic		
Odour threshold:	Not determined.		
 Melting point/freezing point: 	Undetermined.		
 Boiling point or initial boiling point and boiling 			
range	78-118 °C		
· Flammability	Not applicable.		
 Lower and upper explosion limit 			
· Lower:	Not determined.		
· Upper:	Not determined.		
· Flash point:	42 °C		
Decomposition temperature:	Not determined.		
· pH at 20 °C	7.9		
· Viscosity:			
· Kinematic viscosity	Not determined.		
· Kinematic: 23 °C - 4 mm (ISO 2431)			
· Dynamic:	Not determined.		
· Solubility			
· water:	Fully miscible.		
· Partition coefficient n-octanol/water (log value)	Not determined.		
· Vapour pressure:	Not determined.		
· Density and/or relative density			
· Density at 20 °C:	0.98 g/cm ³		
· Relative density	Not determined.		
· Vapour density	Not determined.		
vapour density	Not determined.		
• 9.2 Other information			
· Appearance:			
· Form:	Fluid		



Printing date 12.03.2024

Version number 304 (replaces version 303)

Revision: 12.03.2024

Trade name: Rust Converter E-COLL

	(Contd. of page 6)
 Important information on protection of health 	
and environment, and on safety.	
 Ignition temperature: 	Product is not selfigniting.
 Explosive properties: 	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
 Solvent separation test: 	
· Organic solvents:	10.1 %
· VOC (EC) %	140,1 g/l
· VOC (EC) g/l	
· VOCV (CH)	14,30 %
 Change in condition 	
· Drip point:	
 Oxidising properties 	Not determined.
 Evaporation rate 	Not determined.
Information with regard to physical hazard	
classes	
Explosives	Void
· Flammable gases	Void
Aerosols	Void
 Oxidising gases 	Void
 Gases under pressure 	Void
 Flammable liquids 	Flammable liquid and vapour.
· Flammable solids	Void
 Self-reactive substances and mixtures 	Void
 Pyrophoric liquids 	Void
· Pyrophoric solids	Void
 Self-heating substances and mixtures 	Void
· Substances and mixtures, which emit flammabl	
gases in contact with water	Void
 Oxidising liquids 	Void
· Oxidising solids	Void
 Organic peroxides 	Void
 Corrosive to metals 	Void
 Desensitised explosives 	Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.



Printing date 12.03.2024

Version number 304 (replaces version 303)

Revision: 12.03.2024

Trade name: Rust Converter E-COLL

(Contd. of page 7)

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
CAS: 64-17-5 ethanol			
Oral	LD50	10,470 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat)	
Inhalative	LC50/4h	38 ppm (rat)	
CAS: 78-93-3 butanone			
Oral	LD50	3,300 mg/kg (rat)	
Dermal	LD50	5,000 mg/kg (rabbit)	

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

• Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

• STOT-single exposure Based on available data, the classification criteria are not met.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

 \cdot 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:				
CAS: 64-17-5 ethanol				
L	_C50 (96h) (dynamic)	15,300 mg/L (Pimephales promelas)		
L	_C50/48h (dynamic)	5,012 mg/l (Daphnia galeata)		
CAS: 78-93-3 butanone				
Inhalative L	_C50	2,993 mg/L (Lepomis macrochirus)		
		(Contd. on page 9)		



Printing date 12.03.2024

Version number 304 (replaces version 303)

Revision: 12.03.2024

Trade name: Rust Converter E-COLL

(Contd. of page 8)

- **12.2 Persistence and degradability** No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

- · European waste catalogue
- 07 07 99 wastes not otherwise specified
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- · 14.1 UN number or ID number
- \cdot ADR, IMDG, IATA
- · 14.2 UN proper shipping name
- · ADR
- · IMDG, IATA
- · 14.3 Transport hazard class(es)
- · ADR, IMDG, IATA



- Class
- Label

UN1993

UN1993 FLAMMABLE LIQUID, N.O.S. FLAMMABLE LIQUID, N.O.S.

3 Flammable liquids.

3

(Contd. on page 10)



Printing date 12.03.2024 Version number 304 (replaces version 303) Revision: 12.03.2024

Trade name: Rust Converter E-COLL

	(Contd. of page 9)
· 14.4 Packing group · ADR, IMDG, IATA	III
 • 14.5 Environmental hazards: • Marine pollutant: 	No
 • 14.6 Special precautions for user • Hazard identification number (Kemler code): • EMS Number: 	Warning: Flammable liquids. 30 F-E,S-D
 • 14.7 Maritime transport in bulk according to IMO instruments 	Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) Transport category Tunnel restriction code UN "Model Regulation": 	5L 3 D/E UN1993, FLAMMABLE LIQUID, N.O.S., 3, III

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



· Signal word Warning

· Hazard statements

H226 Flammable liquid and vapour.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 11)

EU ----



Printing date 12.03.2024

Version number 304 (replaces version 303)

Revision: 12.03.2024

Trade name: Rust Converter E-COLL

(Contd. of page 10)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

EUH071 Corrosive to the respiratory tract.

· Department issuing SDS: Product safety department

- Contact: Head of Product Safety Department
- Date of previous version: 05.12.2023
- · Version number of previous version: 303

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 3: Acute toxicity - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 2: Acute toxicity - Category 2 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Corr. 1C: Skin corrosion/irritation - Category 1C Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1



Printing date 12.03.2024

Version number 304 (replaces version 303)

Revision: 12.03.2024

Trade name: Rust Converter E-COLL

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

(Contd. of page 11)

- EU ----

 \cdot * Data compared to the previous version altered.