


# LAUFEN INSTALLATION SYSTEM

## CW104

### Concealed frame with cistern and air admittance valve for wallhung WC

## 92010.4



#### TECHNICAL DATA

Order no.	92010.4	Tank	Installation depth: 120 mm, material PP
Certified to	EN 14055	Installation depth	135-205 mm
matching for	All LAUFEN wallhung toilets	Weight	13,0 kg
Specifications	Self-supporting steel frame for covering with plasterboard, installation onto a solid wall, in drywall constructions. With air admittance valve. With front operated. Dual-Flush 6/3-l (4.5/3-l-flush), with water condensation insulation. Fill valve Noise Class I.	Mounting acc. incl.	Wall bracket, protection box for access opening, inspection box for WC connection, retaining bolts with protection plugs, angle valve R 1/2, WC connector 90° (Ø 90 mm), PE transition sleeve Ø 90 / 110 mm, WC connection set Ø 90 mm, L=180 mm, mounting material.
Other specifications	Galvanized leg supports, rotatable, height-adjustable 0-200 mm. Capable to resist 400 kg	Mounting acc. excl.	Sound insulation set, order no. 89269.6
Water inlet	top R 1/2, brass, matching for standard pipe systems	Accessories excl.	Actuator plates dual flush, order no. 90010.0, 90010.1, 90010.2 (glass), 90010.3 (stainless steel), 90010.4, 90010.5, 90010.6, Electronic actuator plate dual flush, order no. 90010.7 (glass)
Outlet	DN 90/110	Mounting information	Height from finished floor to top of WC pre-set to 400 mm.
Flow pressure range	0.5-10 bar	Colours	Surface powder coated blue
Water temperature	max. 25°C		

#### TECHNICAL DRAWINGS / S 1 : 20

