

Data sheet Gebo G316

Gewindefittings aus Edelstahl / Stainless steel threaded fittings

Code 6240

Reduziermuffe – I/I / Reducing Socket – F/F

- Material: 1.4408
- Legierungsbestandteile / Alloying components in %:
C ≤ 0,07 – Cr 18,0-20,0 – Ni 9,0-12,0 – Mo 2,0-2,5
- Anschlussgewinde gemäß / Connection thread according to
DIN EN 10226 (ISO 7/1)



Size (1x2)	Code	mm			kg
		L	Ø D1	Ø D2	
1/4" x 1/8"	6240-014018	25,0	17,5	14,0	0,021
3/8" x 1/8"	6240-038018	23,0	21,0	14,0	0,020
3/8" x 1/4"	6240-038014	26,0	21,0	17,5	0,026
1/2" x 1/8"	6240-012018	34,0	26,5	14,0	0,046
1/2" x 1/4"	6240-012014	34,0	26,5	17,5	0,050
1/2" x 3/8"	6240-012038	34,0	26,5	21,0	0,051
3/4" x 1/8"	6240-034018	36,0	32,0	14,0	0,052
3/4" x 1/4"	6240-034014	36,0	32,0	17,5	0,066
3/4" x 3/8"	6240-034038	36,0	32,0	21,0	0,055
3/4" x 1/2"	6240-034012	36,0	32,0	25,5	0,073
1" x 3/8"	6240-100038	42,0	39,0	21,0	0,108
1" x 1/2"	6240-100012	42,0	39,0	25,5	0,110
1" x 3/4"	6240-100034	42,0	39,0	31,0	0,124
1 1/4" x 1/2"	6240-114012	48,0	48,0	25,5	0,154
1 1/4" x 3/4"	6240-114034	48,0	48,0	31,0	0,163
1 1/4" x 1"	6240-114100	48,0	48,0	39,0	0,174
1 1/2" x 1/2"	6240-112012	52,0	54,0	25,5	0,155
1 1/2" x 3/4"	6240-112034	52,0	54,0	31,0	0,162
1 1/2" x 1"	6240-112100	52,0	54,0	39,0	0,243
1 1/2" x 1 1/4"	6240-112114	52,0	54,0	48,0	0,180
2" x 1/2"	6240-200012	58,0	67,5	25,5	0,225
2" x 3/4"	6240-200034	58,0	67,5	31,0	0,329
2" x 1"	6240-200100	58,0	67,5	39,0	0,347
2" x 1 1/4"	6240-200114	58,0	67,5	48,0	0,360
2" x 1 1/2"	6240-200112	58,0	67,5	54,0	0,345
2 1/2" x 1 1/2"	6240-212112	65,0	84,0	54,0	0,470
2 1/2" x 2"	6240-212200	65,0	84,0	67,5	0,567
3" x 2"	6240-300200	72,0	98,0	67,5	0,800
3" x 2 1/2"	6240-300212	72,0	98,0	84,0	0,856
4" x 2"	6240-400200	94,0	125,0	67,5	1,009
4" x 2 1/2"	6240-400212	94,0	125,0	84,0	1,028
4" x 3"	6240-400300	94,0	125,0	98,0	1,086

