

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.01.2021

Version number 304

Revision: 20.01.2021

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier** 600166
- **Trade name:** PU-2K-Schaum B2 E-COLL
- **Article number:** 4317784150897
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**  
SU21 Consumer uses: Private households / general public / consumers  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture**  
Sealant  
Adhesives
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH  
EDE Platz 1  
D-42389 Wuppertal  
Germany  
  
Tel. +49 202 6096-0  
e-mail: sdb@ede.de
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Carc. 2	H351	Suspected of causing cancer.
STOT SE 3	H335	May cause respiratory irritation.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.01.2021

Version number 304

Revision: 20.01.2021

**Trade name: PU-2K-Schaum B2 E-COLL**

(Contd. of page 1)

**· Hazard pictograms**

GHS02 GHS07 GHS08

**· Signal word** Danger**· Hazard-determining components of labelling:**

diphenylmethanediisocyanate, isomers and homologues

**· Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.

**· Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P405 Store locked up.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Additional information:**

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

**· 2.3 Other hazards****· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 20.01.2021

Version number 304

Revision: 20.01.2021

Trade name: PU-2K-Schaum B2 E-COLL









(Contd. of page 2)

### SECTION 3: Composition/information on ingredients

#### · 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

#### · **Dangerous components:**

CAS: 9016-87-9 Reg.nr.: 01-2119457024-46-xxxx	diphenylmethanediisocyanate, isomeres and homologues  Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373  Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	>10-<25%
CAS: 107-21-1 EINECS: 203-473-3 Index number: 603-027-00-1 Reg.nr.: 01-2119456816-28-xxxx	ethanediol  STOT RE 2, H373  Acute Tox. 4, H302	>5-<10%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8	dimethyl ether  Flam. Gas 1A, H220 Press. Gas (Comp.), H280 EUH044	>5-<10%
CAS: 1244733-77-4 EC number: 807-935-0	Reaction products of phosphoryl trichloride and 2-methyloxirane  Acute Tox. 4, H302	>10-<20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane  Flam. Gas 1A, H220 Press. Gas (Comp.), H280	>2.5-<5%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane  Flam. Gas 1A, H220	>5-<10%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

##### · **General information:**

Personal protection for the First Aider.  
Immediately remove any clothing soiled by the product.

##### · **After inhalation:**

Supply fresh air.  
Seek medical treatment in case of complaints.

##### · **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.01.2021

Version number 304

Revision: 20.01.2021

**Trade name: PU-2K-Schaum B2 E-COLL**

(Contd. of page 3)

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.  
Seek immediate medical advice.

· **4.2 Most important symptoms and effects, both acute and delayed**

Dizziness

Headache

Dizziness

Allergic reactions

Unconsciousness

· **Hazards** Danger of impaired breathing.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures**

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

Nitrogen oxides (NO<sub>x</sub>)

In case of fire, the following can be released:

Hydrogen chloride (HCl)

Hydrogen cyanide (HCN)

· **5.3 Advice for firefighters**

· **Protective equipment:**

Do not inhale explosion gases or combustion gases.

Mouth respiratory protective device.

· **Additional information** Cool endangered receptacles with water spray.

**SECTION 6: Accidental release measures**

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

· **6.3 Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.01.2021

Version number 304

Revision: 20.01.2021

**Trade name: PU-2K-Schaum B2 E-COLL**

(Contd. of page 4)

Do not flush with water or aqueous cleansing agents  
Dispose contaminated material as waste according to item 13.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Open and handle receptacle with care.  
Use only in well ventilated areas.  
Keep away from heat and direct sunlight.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Do not spray onto a naked flame or any incandescent material.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**

Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.

**Information about storage in one common storage facility:** Store away from oxidising agents.

**Further information about storage conditions:** Keep container tightly sealed.

**7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****CAS: 107-21-1 ethanediol**

IOELV	Short-term value: 104 mg/m <sup>3</sup> , 40 ppm
	Long-term value: 52 mg/m <sup>3</sup> , 20 ppm
	Skin

**CAS: 115-10-6 dimethyl ether**

IOELV	Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm
-------	--

**Additional information:** The lists valid during the making were used as basis.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.01.2021

Version number 304

Revision: 20.01.2021

**Trade name: PU-2K-Schaum B2 E-COLL**

(Contd. of page 5)

**· 8.2 Exposure controls****· Appropriate engineering controls** No further data; see item 7.**· Individual protection measures, such as personal protective equipment****· General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes.

Keep away from foodstuffs, beverages and feed.

**· Respiratory protection:**

The selection of respiratory protection masks (EN 14387) must be based on the known or expected concentrations, the dangers of the product and the occupational exposure limit values (Section 8.1) of the respective respiratory protection mask.

Short term filter device:

Filter A/P2

**· Hand protection**

Protective gloves

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· For the permanent contact gloves made of the following materials are suitable:**

Viton

Penetration time (min.) : &gt;30 min.

Recommended thickness of the material:  $\geq 0.4$  mm**· As protection from splashes gloves made of the following materials are suitable:**

Butyl rubber, BR

Recommended thickness of the material:  $\geq 0.1$  mm**· Eye/face protection** Recommendation: safety glasses with side protection shield**· Body protection:**

Protective work clothing

Workwear (e.g. safety shoes according to EN ISO 20345, long-sleeved work clothes, long trousers).

**SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information****· Colour:**

Colourless

**· Odour:**

Characteristic

**· Odour threshold:**

Not determined.

**· Melting point/freezing point:**

Undetermined.

**· Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol.

**· Flammability**

Not applicable.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.01.2021

Version number 304

Revision: 20.01.2021

**Trade name: PU-2K-Schaum B2 E-COLL**

(Contd. of page 6)

- **Lower and upper explosion limit**
- **Lower:** Not determined.
- **Upper:** Not determined.
- **Flash point:** Not applicable, as aerosol.
- **Auto-ignition temperature:** Product is not selfigniting.
- **Decomposition temperature:** Not determined.
- **pH** Not determined.
- **Viscosity:**
- **Kinematic viscosity** Not determined.
- **Kinematic: 23 °C - 4 mm (ISO 2431)**
- **Dynamic:** Not determined.
- **Solubility**
- **water:** Not miscible or difficult to mix.
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Vapour pressure at 20 °C:** 5,100 hPa
- **Density and/or relative density**
- **Density at 20 °C:** 1.01 g/cm<sup>3</sup>
- **Relative density** Not determined.
- **Vapour density** Not determined.
  
- **9.2 Other information**
- **Appearance:**
- **Form:** Aerosol
- **Important information on protection of health and environment, and on safety.**
- **Explosive properties:** Not determined.
- **Solvent separation test:**
- **VOC (EC) %** 18.25 %
- **Change in condition**
- **Softening point/range**
- **Oxidising properties** Not determined.
- **Evaporation rate** Not applicable.
  
- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols**  
Extremely flammable aerosol. Pressurised container: May burst if heated.
  
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.01.2021

Version number 304

Revision: 20.01.2021

**Trade name: PU-2K-Schaum B2 E-COLL**· **Desensitised explosives**

Void

(Contd. of page 7)

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**  
Danger of receptacles bursting because of high vapour pressure when heated.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:****CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

Oral	LD50	10,000 mg/kg (rat) (Literatur)
Dermal	LD50	>5,000 mg/kg (rabbit) (Literatur)
Inhalative	LC50/4h	11 mg/m <sup>3</sup> (rat)

**CAS: 107-21-1 ethanediol**

Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	9,530 mg/kg (rabbit)

**CAS: 74-98-6 propane**

Inhalative	LC50/4h	>20 mg/m <sup>3</sup> (rat)
------------	---------	-----------------------------

- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation**  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.01.2021

Version number 304

Revision: 20.01.2021

**Trade name: PU-2K-Schaum B2 E-COLL**

(Contd. of page 8)

- **Carcinogenicity**  
Suspected of causing cancer.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause respiratory irritation.
- **STOT-repeated exposure**  
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

**11.2 Information on other hazards****· Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information****· 12.1 Toxicity****· Aquatic toxicity:****CAS: 75-28-5 isobutane**

EC50 (48h) 69.43 mg/L (daphnia)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods:**  
Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste.  
Observe local regulations.

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.01.2021

Version number 304

Revision: 20.01.2021

**Trade name: PU-2K-Schaum B2 E-COLL**

(Contd. of page 9)

· European waste catalogue	
16 05 04*	gases in pressure containers (including halons) containing hazardous substances
08 05 01*	waste isocyanates
15 01 10*	packaging containing residues of or contaminated by hazardous substances

**SECTION 14: Transport information**

- 14.1 UN number or ID number
- ADR, IMDG, IATA UN1950
- 14.2 UN proper shipping name
- ADR UN1950 AEROSOLS
- IMDG, IATA AEROSOLS
- 14.3 Transport hazard class(es)
- ADR



- Class 2 5F Gases.
- Label 2.1

- IMDG, IATA



- Class 2 Gases.
- Label 2.1

- 14.4 Packing group
- ADR, IMDG, IATA Void

- 14.5 Environmental hazards:
- Marine pollutant: No

- 14.6 Special precautions for user Warning: Gases.
- EMS Number: F-D,S-U

- 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

- Transport/Additional information:

- ADR
- Limited quantities (LQ) 1L
- Transport category 2
- Tunnel restriction code D

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.01.2021

Version number 304

Revision: 20.01.2021

**Trade name: PU-2K-Schaum B2 E-COLL**

(Contd. of page 10)

· **UN "Model Regulation":** UN1950, AEROSOLS, 2.1**SECTION 15: Regulatory information**

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Information about limitation of use:**  
Employment restrictions concerning pregnant and lactating women must be observed.
- **Exposure scenario(s)**  
Exposure scenario(s) of ingredients (if present) are available on request at:  
sdb@ede.de

**\* SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
  - H220 Extremely flammable gas.
  - H280 Contains gas under pressure; may explode if heated.
  - H302 Harmful if swallowed.
  - H315 Causes skin irritation.
  - H317 May cause an allergic skin reaction.
  - H319 Causes serious eye irritation.
  - H332 Harmful if inhaled.
  - H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
  - H335 May cause respiratory irritation.
  - H351 Suspected of causing cancer.
  - H373 May cause damage to organs through prolonged or repeated exposure.
  - EUH044 Risk of explosion if heated under confinement.
  - EUH204 Contains isocyanates. May produce an allergic reaction.
- **Training hints** As from 24 August 2023 adequate training is required before industrial or professional use.
- **Date of previous version:** 20.01.2021
- **Version number of previous version:** 303
- **Abbreviations and acronyms:**
  - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - IATA: International Air Transport Association
  - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - VOC: Volatile Organic Compounds (USA, EU)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - Flam. Gas 1A: Flammable gases – Category 1A
  - Aerosol 1: Aerosols – Category 1
  - Press. Gas (Comp.): Gases under pressure – Compressed gas
  - Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 12)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 20.01.2021

Version number 304

Revision: 20.01.2021

---

**Trade name: PU-2K-Schaum B2 E-COLL**

---

(Contd. of page 11)

Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Resp. Sens. 1: Respiratory sensitisation – Category 1  
Skin Sens. 1: Skin sensitisation – Category 1  
Carc. 2: Carcinogenicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· \* **Data compared to the previous version altered.**

---

EU