

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.04.2024

Version number 305 (replaces version 304)

Revision: 03.04.2024

### \* SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### · 1.1 Product identifier

· Trade name: Rust Converter E-COLL

· Article number: 4317784499910

· UFI: J6YQ-546X-XCOM-RV1H

#### · 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Application of the substance / the mixture Penetrating oil

· Uses advised against Food

#### · 1.3 Details of the supplier of the safety data sheet

##### · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH

EDE Platz 1

D-42389 Wuppertal

Germany

Tel. +49 202 6096-0

e-mail: sdb@ede.de

· Further information obtainable from: Product safety department

· 1.4 Emergency telephone number: Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

### \* SECTION 2: Hazards identification

#### · 2.1 Classification of the substance or mixture

##### · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### · 2.2 Label elements

##### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.04.2024

Version number 305 (replaces version 304)

Revision: 03.04.2024

**Trade name: Rust Converter E-COLL**

(Contd. of page 1)

**· Hazard pictograms**

GHS02 GHS07

**· Signal word** Danger**· Hazard-determining components of labelling:**reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)**· Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

**· Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Additional information:** Formation of explosive mixtures possible without adequate ventilation.**· 2.3 Other hazards****· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.**\* SECTION 3: Composition/information on ingredients****· 3.2 Mixtures****· Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.04.2024

Version number 305 (replaces version 304)

Revision: 03.04.2024

**Trade name: Rust Converter E-COLL**

(Contd. of page 2)

· <b>Dangerous components:</b>		
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether ⚠ Flam. Gas 1A, H220 ⚠ Press. Gas (Comp.), H280	30-50%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	1-10%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119486136-34	xylene ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335	1-10%
CAS: 111-76-2 EINECS: 203-905-0 Index number: 603-014-00-0 Reg.nr.: 01-2119475108-36-xxxx	2-butoxyethanol ⚠ Acute Tox. 3, H311; Acute Tox. 3, H331 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg LC50/4h inhalative: 3 ppm	1-10%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700) ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 EUH205 Specific concentration limits: Eye Irrit. 2; H319: C $\geq$ 5 % Skin Irrit. 2; H315: C $\geq$ 5 %	1-10%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx 01-2119485493-29-0059	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336 EUH066	1-10%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ STOT SE 3, H335-H336 EUH066	2.5-10%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38-xxxx	butan-1-ol ⚠ Flam. Liq. 3, H226 ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-10%

· **Regulation (EC) No 648/2004 on detergents / Labelling for contents**

less than 5 %  
aromatic hydrocarbons  
aliphatic hydrocarbons

&lt;5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.04.2024

Version number 305 (replaces version 304)

Revision: 03.04.2024

**Trade name: Rust Converter E-COLL**

(Contd. of page 3)

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
  - **General information:**  
Personal protection for the First Aider.  
Immediately remove any clothing soiled by the product.
  - **After inhalation:**  
Supply fresh air.  
Seek medical treatment in case of complaints.
  - **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.
  - **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
  - **After swallowing:**  
Rinse out mouth and then drink plenty of water.  
If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
  - **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
  - **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Can form explosive gas-air mixtures.
- **5.3 Advice for firefighters**
  - **Protective equipment:** Do not inhale explosion gases or combustion gases.
  - **Additional information**  
Cool endangered receptacles with water spray.  
Collect contaminated fire fighting water separately. It must not enter the sewage system.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.

(Contd. on page 5)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.04.2024

Version number 305 (replaces version 304)

Revision: 03.04.2024

---

**Trade name: Rust Converter E-COLL**

---

(Contd. of page 4)

Ensure adequate ventilation

**· 6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.

**· 6.3 Methods and material for containment and cleaning up:**

Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents

**· 6.4 Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

---

**SECTION 7: Handling and storage**

---

**· 7.1 Precautions for safe handling**

Open and handle receptacle with care.  
Use only in well ventilated areas.

**· Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

**· 7.2 Conditions for safe storage, including any incompatibilities****· Storage:****· Requirements to be met by storerooms and receptacles:**

Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.

**· Information about storage in one common storage facility:** Store away from oxidising agents.**· Further information about storage conditions:**

Keep container tightly sealed.  
Protect from heat and direct sunlight.

**· 7.3 Specific end use(s)** No further relevant information available.

---

EU  
(Contd. on page 6)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.04.2024

Version number 305 (replaces version 304)

Revision: 03.04.2024

**Trade name: Rust Converter E-COLL**

(Contd. of page 5)

### \* SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

##### · Ingredients with limit values that require monitoring at the workplace:

###### CAS: 115-10-6 dimethyl ether

IOELV	Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm
-------	--

###### CAS: 1330-20-7 xylene

IOELV	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Skin
-------	--

###### CAS: 111-76-2 2-butoxyethanol

IOELV	Short-term value: 246 mg/m <sup>3</sup> , 50 ppm Long-term value: 98 mg/m <sup>3</sup> , 20 ppm Skin
-------	--

###### CAS: 123-86-4 n-butyl acetate

IOELV	Short-term value: 723 mg/m <sup>3</sup> , 150 ppm Long-term value: 241 mg/m <sup>3</sup> , 50 ppm
-------	--

#### · DNELs

##### CAS: 67-63-0 propan-2-ol

Inhalative	DNEL (worker)	500 mg/m <sup>3</sup> (Workers)
	DNEL (population)	89 mg/m <sup>3</sup> (cus)

· **Additional information:** The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

##### · **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

The usual precautionary measures are to be adhered to when handling chemicals.

##### · **Respiratory protection:**

Not necessary if room is well-ventilated.

Respiratory protection is not required when used properly and under normal conditions.

##### · **Hand protection**



Protective gloves

##### · **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4$  mm

(Contd. on page 7)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.04.2024

Version number 305 (replaces version 304)

Revision: 03.04.2024

**Trade name: Rust Converter E-COLL**

(Contd. of page 6)

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye/face protection**

Tightly sealed goggles

**· Body protection: Protective work clothing****SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information**

- **Colour:** Light beige
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.
- **Boiling point or initial boiling point and boiling range** Not applicable, as aerosol.
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
- **Lower:** 1.1 Vol %
- **Upper:** 18.6 Vol %
- **Flash point:** -41 °C
- **Auto-ignition temperature:** 235 °C
- **Decomposition temperature:** Not determined.
- **pH** Not determined.
- **Viscosity:**
- **Kinematic viscosity** Not determined.
- **Kinematic: 23 °C - 4 mm (ISO 2431)**
- **Dynamic:** Not determined.
- **Solubility**
- **water:** Not miscible or difficult to mix.
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Vapour pressure at 20 °C:** 6,000 hPa
- **Density and/or relative density**
- **Density at 20 °C:** 0.77 g/cm<sup>3</sup>
- **Relative density** Not determined.
- **Vapour density** Not determined.

**· 9.2 Other information**

- **Appearance:**
- **Form:** Aerosol
- **Important information on protection of health and environment, and on safety.**
- **Ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Not determined.
- **Solvent separation test:**
- **Organic solvents:** 67.8 %

(Contd. on page 8)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.04.2024

Version number 305 (replaces version 304)

Revision: 03.04.2024

**Trade name: Rust Converter E-COLL**

(Contd. of page 7)

· Water:	20 %
· VOC (EC) %	67.75 %
· Change in condition	
· Drip point:	
· Oxidising properties	Not determined.
· Evaporation rate	Not applicable.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### \* SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 9)



## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.04.2024

Version number 305 (replaces version 304)

Revision: 03.04.2024

**Trade name: Rust Converter E-COLL**

(Contd. of page 8)

<b>· LD/LC50 values relevant for classification:</b>		
<b>CAS: 115-10-6 dimethyl ether</b>		
Inhalative	LC50/4h	308 ppm (rat)
<b>CAS: 67-63-0 propan-2-ol</b>		
Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4h	30 ppm (rat)
<b>CAS: 1330-20-7 xylene</b>		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
<b>CAS: 111-76-2 2-butoxyethanol</b>		
Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4h	3 ppm (ATE)
<b>CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)</b>		
Oral	LD50	11,400 mg/kg (rat)
Dermal	LD50	22,800 mg/kg (rabbit) (GESTIS)
<b>CAS: 123-86-4 n-butyl acetate</b>		
Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4h	>21 ppm (rat)
<b>CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.</b>		
Oral	LD50	3,592 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rabbit)
<b>CAS: 71-36-3 butan-1-ol</b>		
Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4h	8,000 ppm (rat)

**· Skin corrosion/irritation**

Causes skin irritation.

**· Serious eye damage/irritation**

Causes serious eye irritation.

**· Respiratory or skin sensitisation**

May cause an allergic skin reaction.

**· Germ cell mutagenicity** Based on available data, the classification criteria are not met.**· Carcinogenicity** Based on available data, the classification criteria are not met.**· Reproductive toxicity** Based on available data, the classification criteria are not met.**· STOT-single exposure** Based on available data, the classification criteria are not met.

(Contd. on page 10)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.04.2024

Version number 305 (replaces version 304)

Revision: 03.04.2024

**Trade name: Rust Converter E-COLL**

(Contd. of page 9)

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

**· Endocrine disrupting properties**

None of the ingredients is listed.

**\* SECTION 12: Ecological information****· 12.1 Toxicity****· Aquatic toxicity:****CAS: 67-63-0 propan-2-ol**

EC50/24h &gt;10,000 mg/l (daphnia)

**CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )**

EC50 (48h) 2.8 mg/L (daphnia)

96h LC50 3.6 mg/l (Leuciscus idus auratus)

**CAS: 123-86-4 n-butyl acetate**

LC50 (96h) 18 mg/L (Pimephales promelas)

EC50 (48h) 44 mg/L (Daphnia magna)

EC50/24h 73 mg/l (Daphnia magna)

EC50/72h 647.7 mg/l (S)

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

**· 12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

**· 12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**· 12.7 Other adverse effects****· Additional ecological information:****· General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.04.2024

Version number 305 (replaces version 304)

Revision: 03.04.2024

**Trade name: Rust Converter E-COLL**

(Contd. of page 10)

### SECTION 13: Disposal considerations

**13.1 Waste treatment methods:**

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

**European waste catalogue**

15 01 10*	packaging containing residues of or contaminated by hazardous substances
15 01 04	metallic packaging

### SECTION 14: Transport information

**14.1 UN number or ID number****ADR, IMDG, IATA** UN1950**14.2 UN proper shipping name****ADR** UN1950 AEROSOLS  
**IMDG, IATA** AEROSOLS**14.3 Transport hazard class(es)****ADR****Class** 2.5F Gases.  
**Label** 2.1**IMDG, IATA****Class** 2 Gases.  
**Label** 2.1**14.4 Packing group****ADR, IMDG, IATA** Void**14.5 Environmental hazards:****Marine pollutant:** No**14.6 Special precautions for user****Hazard identification number (Kemler code):** -**EMS Number:** F-D,S-U**Stowage Code** SW1 Protected from sources of heat.  
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.**Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:

(Contd. on page 12)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.04.2024

Version number 305 (replaces version 304)

Revision: 03.04.2024

**Trade name: Rust Converter E-COLL**

(Contd. of page 11)

- Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.  
For AEROSOLS with a capacity above 1 litre:  
Segregation as for the appropriate subdivision of class 2.  
For WASTE AEROSOLS:  
Segregation as for the appropriate subdivision of class 2.

- **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

**• Transport/Additional information:**

- **ADR**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity
- **Transport category** 2
- **Tunnel restriction code** D

- **IMDG**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity
- **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

**\* SECTION 15: Regulatory information**

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.

**• Hazard pictograms**

GHS02 GHS07

- **Signal word** Danger

- **Hazard-determining components of labelling:**  
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )

**• Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.

**• Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

(Contd. on page 13)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.04.2024

Version number 305 (replaces version 304)

Revision: 03.04.2024

**Trade name: Rust Converter E-COLL**

(Contd. of page 12)

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing spray.
P280	Wear protective gloves / eye protection / face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P362+P364	Take off contaminated clothing and wash it before reuse.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P321	Specific treatment (see on this label).
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

• **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

• **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

• **REGULATION (EU) 2019/1148**

• **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

• **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

• **Exposure scenario(s)**

Exposure scenario(s) of ingredients (if present) are available on request at:  
sdb@ede.de

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Relevant phrases**

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

(Contd. on page 14)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 03.04.2024

Version number 305 (replaces version 304)

Revision: 03.04.2024

---

**Trade name: Rust Converter E-COLL**

---

(Contd. of page 13)

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

• **Date of previous version:** 23.02.2021

• **Version number of previous version:** 304

• **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

• **\* Data compared to the previous version altered.**

---